



Step Lift Platform Specification

- Load: 250kg
- Drive: Electro-hydraulic
- Speed: 0.25m/sec
- Travel: Max 1m
- Power: 240v 1ph 50Hz 10A
- Stops: 2
- Colour: Platform = RAL 9006 (std)
Gate section = RAL 9006 (std)
(other RAL colours available)
- Gate Section: Glazed as standard
- Gate Handing: Left hand or Right hand
- Upper Call Station: Mounted on gate post
- Lower Call Station: Wall mounted
- External Pump Box: Required for less than 400mm travel

Building work required

- 1 - Provide power supply
- 2 - Provide upper floor adequate for fixing the gate section
- 3 - Provide finish flooring on lower and upper level
- 4 - Provide conduit for cables

<p>Platform Lift Company</p> <p>Apsley Barns, Apsley, Near Andover, Hants, SP11 6NA Tel - 01256 896000 Fax - 01256 896900 E-mail - info@platformliftco.co.uk website - www.platformliftco.co.uk</p>		<p>TITLE E-TYPE Independence Step Lift - Through</p>
<p>DWG NO. 250 - E-TYPE INDEPENDENCE THR</p>	<p>SCALE NTS</p>	<p>DATE 6/5/08</p>
<p>REV B</p>	<p>DRAWN CR</p>	